Packaged Conveying Systems MAXimized.

SINGLE SOURCE CUSTOM ENGINEERING APPLICATION EXPERTISE

GLOBAL SERVICE & SUPPORT 100% GUARANTEED SINCE 1954

Signature Series[™] Vacuum Conveying Systems

Convenience. Performance. Guaranteed.

VAC-U-MAX SIGNATURE SERIES[™] VACUUM CONVEYING SYSTEMS

Our Signature Series[™] line of vacuum conveying systems offer quick and easy vacuum conveying solutions for applications in the food, pharmaceutical, chemical, nonwovens and plastics industries, for free-flowing & non-free flowing powders and granular materials. With over 65 years of experience in pneumatic conveying, handling over 10,000 various powders and granular materials, VAC-U-MAX has built a reputation focused on simple operation with high-power and reliable performance.

Signature Series Packages Include:

- VAC-U-MAX Signature Series Receiver (1500 or 3500 Series)
- UL-Listed Controls
- 15' of Flexible Convey Hose Optional Rigid Tubing
- Convey Wand, Optional Dump Stations
 or Bulk Bag Unloaders
- Uni-Filter or Cartridge Filters
- Vacuum Producer

RECEIVER STYLE VS. MATERIALS CONVEYED

Man Plan	1500 SERIES		3500 SERIES	
	TUBE	CONE	TUBE	CONE
Free Flowing Powders & Granulars	\checkmark	\checkmark	\checkmark	\checkmark
Non-free Flowing Powders & Granulars		\checkmark	\checkmark	\checkmark
Non-free Flowing, High Moisture & Fat Content, Fibrous	\checkmark	X	\checkmark	X

Signature Series[™]1500

UNI-FILTER OR CARTRIDGE

CONVEY RATE: 1500 lbs/hr (680 kg/hr)

- MATERIALS HANDLED: Designed to handle free-flowing to non-free flowing powders, pellets, pastilles, flakes, fibers, hygroscopic materials, food ingredients, and many other granular materials including materials with high moisture.
- RECEIVER DIAMETER: 12 inches (300mm)
- DISCHARGE OPENING: 6 inches (150mm)
- **RECEIVER STYLE:** 70 degree Offset Cone or Tube Style
- VACUUM PRODUCER: Compressed Air or Electric Blower
- FILTER MEDIA: Polyester Felt with PTFE Coating
- MATERIAL OF CONSTRUCTION: 316L Stainless Steel
- MOUNTING OPTIONS: Two Support Ears, Optional Suspension Frame or Bottom Flange Mounted
- **DESIGN OPTIONS:** General Purpose or Sanitary

UNI-FILTER OR CARTRIDGE

16 INCH (400 MM) RECEIVER BODY

AVAILABLE IN OFFSET CONE OR TUBE

> 8 INCH (150 MM) DISCHARGE VALVE



VAC-U-MAX

TOP

AVAILABLE IN OFFSET CONE OR TUBE

6 INCH (150 MM) DISCHARGE VALVE

Signature Series[™] 3500

CONVEY RATE: Up to 3500 lbs/hr (1600 kg/hr)

MATERIALS HANDLED: Designed to handle free-flowing to non-free flowing powders, pellets, pastilles, flakes, fibers, hygroscopic materials, food ingredients, and many other granular materials including materials with high moisture, fat or fibrous content.

RECEIVER DIAMETER: 16 inches (400mm)

DISCHARGE OPENING: 8 inches (200mm)

- **RECEIVER STYLE:** 70 degree Offset Cone or Tube Style
- VACUUM PRODUCER: Compressed Air, Positive Displacement Vacuum Pump or Regen Blower

FILTER MEDIA: Polyester Felt with PTFE Coating

- MATERIAL OF CONSTRUCTION: 316L Stainless Steel
- CONVEYOR MOUNTING CHOICES: Two Ears or Suspension Frame DESIGN OPTIONS: General Purpose or Sanitary

Find out how we can solve all your vacuum conveying challenges, call 800-VAC-U-MAX or visit vac-u-max.com/SignatureSeries.



65 YEARS OF GETTING IT RIGHT.

In material handling solutions, every detail is critical. So when you do business with VAC-U-MAX, you're guaranteed a lot more than a high-performing product: Pioneering materials handling technology. Custom engineering expertise. Rapid turnaround and responsive support. And of course, our 100% satisfaction guarantee.

For more than six decades, we've made a name as a single-source, dedicated provider, handing more types of materials, serving more markets, and offering the highest possible degree of customization—so your systems are maximized to fit your needs.



DELIVERING MORE

GLOBAL SERVICE & SUPPORT 100% GUARANTEED SINCE 1954

vac-u-max.com | 800-VAC-U-MAX

69 William Street · Belleville, New Jersey 07109